



Commercial Supplement

Customer Information:

Entity Name: _____
 Contact Name: _____
 Entity Type: _____

Agent Information:

Agent Name: _____
 Agent Phone: _____
 Agent Email: _____

General Information:

Effective Dates: _____
 New Business or Renewal: _____
 Quote Type: _____

Competing Carrier: _____
 Target (Including Fees & Taxes): \$ _____

Property Information:

	<u>Location/Building 1</u>	<u>Location/Building 2</u>	<u>Location/Building 3</u>
Address			
City/State/Zip			
Distance to Gulf			
Year Built			
<i>Roof Updates</i>			
<i>Wiring Updates</i>			
<i>Plumbing Updates</i>			
<i>HVAC Updates</i>			
Occupancy			
Construction			
Protection Class			
Roof Type			
Roof Shape			
Stories			
Fortified			
Alarm			
Opening Protection			
Percent Occupied			
Structure Type			
Exterior Finish			
Square Footage			
Tenant Type/Mix			

Coverage Information: Location #: _____ Building#: _____

Subject of Insurance	Amount	Coinsurance	Valuation	Causes of Loss	AOP Deductible	Wind/Hail Deductible



Coverage Information: Location #: _____ Building#: _____

Subject of Insurance	Amount	Coinsurance	Valuation	Causes of Loss	AOP Deductible	Wind/Hail Deductible

Coverage Information: Location #: _____ Building#: _____

Subject of Insurance	Amount	Coinsurance	Valuation	Causes of Loss	AOP Deductible	Wind/Hail Deductible

Notes:

- Frame Exterior walls are wood or other combustible material including brick veneer, stone-veneer, wood iron clad, or stucco on wood.
- Joisted Masonry (JM) Exterior walls are masonry, such as brick, concrete, gypsum block, hollow concrete block, stone, tile, where roof and floors are combustible
- Non-Combustible (NC) Exterior walls, floors, and roof are metal, gypsum, or other non combustible material
- Masonry Non-Combustible (MNC) Exterior walls are same as (JM), but the floors and roof are metal, or other non-combustible material
- Modified Fire Resistive (MFR) Exterior walls, floors, and roof are masonry of fire resistive having a fire resistive rating of less than 2 hours
- Fire Resistive (FR) Exterior walls, floors and roof are masonry of fire resistive having a fire resistive rating of more than 2 hours